








Illuminated pushbutton actuator, Flat, momentary, 1 N/O, Screw connection, LED green, Without button plate, 120 V AC, Bezel: black

Part no. C22S-DL-XG-K10-120
Catalog No. 121692
Alternate Catalog No. C22S-DL-XG-K10-120

Delivery program

| | | | |
|---|--|--|--|
| Product range | | | RMQ Compact |
| Basic function | | | Illuminated pushbutton actuators |
| Single unit/Complete unit | | | Complete unit |
| Design | | | Flat |
| | | | momentary |
| Connection type | | | Screw connection |
| Colour | | | |
| LED | | |  |
| LED | | | green |
| Button plate | | | |
| button plate | | | Without button plate |
| Rated operational voltage LED | | | 120 V AC |
| Degree of Protection | | | IP66, IP67, IP69 |
| Front ring | | | Bezel: black |
| Connection to SmartWire-DT | | | no |
| Contacts | | | |
| N/O = Normally open | | | 1 N/O |
| Contact sequence | | |  |
| Contact travel  = Contact closed  = Contact open | | | |
| Contact diagram | | |  |

Technical data

| | | | |
|----------------------|--------------|-------------------|--|
| General | | | |
| Standards | | | IEC/EN 60947-5-1 VDE 0660 |
| Lifespan, mechanical | Operations | x 10 ⁶ | > 5 |
| Operating frequency | Operations/h | | ≤ 3600 |
| Actuating force | | n | ≤ 5 |
| Climatic proofing | | | Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30 |
| Degree of Protection | | | IP66, IP67, IP69 |
| Ambient temperature | | | |

| | | |
|--------------------------------------|-----------------|-----------------|
| Open | °C | -25 - +70 |
| Storage | °C | - -30 - + 80 |
| Mounting position | | As required |
| Terminal capacities | mm ² | |
| Solid | mm ² | 2 x 0.5 - 1.5_x |
| Flexible with ferrule | mm ² | 2 x 0.5 - 1.5_x |
| Tightening torque for terminal screw | Nm | 0.8 |

Contacts

| | | | |
|---|------------------|-------------------|---------------|
| Rated impulse withstand voltage | U _{imp} | V AC | 4000 |
| Rated insulation voltage | U _i | V | 250 |
| Rated conditional short-circuit current | I _q | kA | 1 |
| Overvoltage category/pollution degree | | | III/3 |
| Control circuit reliability | | | |
| at 24 V DC/5 mA | H _F | Fault probability | values follow |
| at 5 V DC/1 mA | H _F | Fault probability | values follow |
| Max. short-circuit protective device | | | |
| Fuse | gG/gL | A | 10 |

Design verification as per IEC/EN 61439

| | | | |
|--|----|--|-----|
| Technical data for design verification | | | |
| Operating ambient temperature min. | °C | | -25 |
| Operating ambient temperature max. | °C | | 70 |

Technical data ETIM 7.0

| | | | |
|---|----|--|----------------------|
| Low-voltage industrial components (EG000017) / Push button, complete (EC001028) | | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Push-button actuator, complete unit (ecl@ss10.0.1-27-37-12-28 [AKF046014]) | | | |
| Number of command positions | | | 1 |
| Type of button | | | Flat |
| Colour button | | | Without button plate |
| Construction type lens | | | Round |
| Hole diameter | mm | | 22.5 |
| Width opening | mm | | 0 |
| Height opening | mm | | 0 |
| Suitable for illumination | | | Yes |
| Switching function latching | | | No |
| Spring-return | | | Yes |
| Supply voltage lamp | V | | 120 |
| Number of contacts as normally open contact | | | 1 |
| Number of contacts as normally closed contact | | | 0 |
| Number of contacts as change-over contact | | | 0 |
| Type of electric connection | | | Screw connection |
| With front ring | | | Yes |
| Material front ring | | | Plastic |
| Colour front ring | | | Other |
| Degree of protection (IP) | | | Other |
| Degree of protection (NEMA) | | | |

Approvals

| | | | |
|-------------------------|--|--|--|
| Product Standards | | | IEC/EN 60947-5-1; UL 508; CAN/CSA-C22.2 No. 14-05 und 94-M91; CE marking |
| UL File No. | | | E29184 |
| UL Category Control No. | | | NKCR |
| CSA File No. | | | 165628 |
| CSA Class No. | | | 321103 |

| | | |
|-----------------------------|--|--------------------------|
| North America Certification | | UL listed, CSA certified |
| Degree of Protection | | 1,3R,4X,12,13 |

Additional product information (links)

IL04716025Z RMQ-Titan: compact programm

IL04716025Z RMQ-Titan: compact programm https://es-assets.eaton.com/DOCUMENTATION/AWA_INSTRUCTIONS/IL04716025Z2019_05.pdf