



Cassette 2500A, IZMX403 m. control cable connection



Part no. IZMX-CAS403-2500-SEC-1
Catalog No. 183947
Alternate Catalog No. 67C2752A51
EL-Nummer (Norway) 4398356

Delivery program

Product range			Accessories
Accessories			Withdrawable units
Accessories			Cassettes
			Equipment supplied: arcing chamber cover, terminal blocks fully populated
Rated current	I_n	A	2500
Pole			3
For use with			IZMX40...3-...W INX40...3-...W
Instructions			With control conductor terminals fully fitted.
Information about equipment supplied			with arcing chamber cover
			Control circuit terminal
Installation type			Withdrawable


Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Chassis part power circuit breaker (EC002043)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Chassis part circuit breaker (ecl@ss10.0.1-27-37-04-22 [ACN955011])			
Rated current I_n		A	2500
Number of poles			3
Version as busbar adapter			No
Version as built-in device			Yes
Type of electrical connection of main circuit			Rail connection

Dimensions



② Contact surface flange terminal