

Connections, front, 1600A, IZMX16, 3p

Part no. IZMX-TF163-1600-1  
 Catalog No. 183980  
 Alternate Catalog No. 65A2606G11  
 EL-Nummer (Norway) 0004398390

**Delivery program**

Product range			Accessories
Accessories			Main terminal kits
Accessories			Front connections
			This connection kit comes with L-shaped front terminals for connection to the circuit-breaker or the cassette. The circuit-breaker can be connected directly with CU bars on the rear flanged connection. If necessary, the optional front terminals can be installed before the circuit-breaker is installed in the enclosure. This way, the final connection to the circuit-breaker can be made from the front.
Rated current	$I_n$	A	630 - 1600
Pole			3
For use with			IZMX40...3...08W IZMX40...3...10W IZMX40...3...12W IZMX40...3...16W INX40...3...08W INX40...3...10W INX40...3...12W INX40...3...16W
Information about equipment supplied			Each set includes the connections for top and bottom. 3-pole for 6 connections, 4-pole for 8 connections Screws, washers, and supports are included as standard.

**Design verification as per IEC/EN 61439**

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

**Technical data ETIM 7.0**

Low-voltage industrial components (EG000017) / Connection vane/phase spreader (EC002019)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Connection vane/phase spreader (ecl@ss10.0.1-27-37-13-05 [ACN990012])			
Suitable for number of poles			3