



Signalling switch ON-OFF, 2W

Part no. IZMX-AS22-40-1
Catalog No. 184115
Alternate Catalog No. 67C2823G92
EL-Nummer (Norway) 4398478

Delivery program

Product range		Accessories
Accessories		Auxiliary contact
Accessories		Standard auxiliary switch for On-Off signaling
		The basic device already contains two changeover contacts. Mounting kit with 2 additional changeover contacts with cable lengths for IZMX40.
For use with		IZMX40... INX40...
Instructions		Retrofit kit for IZMX40 circuit-breakers The retrofit kit includes the required SEC control cable terminals.
		2 changeover contacts

Technical data

Rated breaking capacity

Inductive load		
250 V AC	A	10
125 V DC	A	0.5
250 V DC	A	0.25

Design verification as per IEC/EN 61439

Technical data for design verification		
Operating ambient temperature min.	°C	-25
Operating ambient temperature max.	°C	70

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Auxiliary contact block (EC000041)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Auxiliary switch block (ec@ss10.0.1-27-37-13-02 [AKN342013])		
Number of contacts as change-over contact		2
Number of contacts as normally open contact		0
Number of contacts as normally closed contact		0
Number of fault-signal switches		
Rated operation current Ie at AC-15, 230 V	A	10
Type of electric connection		Flat plug-in connection
Model		Integrable
Mounting method		Other
Lamp holder		