



Reset remote, 220-240VAC/DC

Part no. IZMX-RR230AD-40-1
Catalog No. 184127
Alternate Catalog No. 68D2806G62
EL-Nummer (Norway) 0004398490

Delivery program

Product range		Accessories
Accessories		Trip indication / Reset options
Accessories		Remote reset
		The circuit-breaker is equipped with a mechanical trip indicator (red pin). After the remote reset coil is electrically actuated, the reclosing lockout can be reset. Cannot be combined with remote reset.
Rated control voltage	U _s V	208 - 240 V AC 50/60 Hz 208 - 250 V DC
For use with		IZMX40...W IZMX40...F
Instructions		The retrofit kit includes the required SEC control cable terminals.

Design verification as per IEC/EN 61439

Technical data for design verification		
Operating ambient temperature min.	°C	-25
Operating ambient temperature max.	°C	70

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Shunt release (for power circuit breaker) (EC001023)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Full load current trip (ecl@ss10.0.1-27-37-04-18 [AKF016013])		
Rated control supply voltage U _s at AC 50HZ	V	208 - 240
Rated control supply voltage U _s at AC 60HZ	V	208 - 240
Rated control supply voltage U _s at DC	V	220 - 250
Voltage type for actuating		AC/DC
Initial value of the undelayed short-circuit release - setting range	A	0
End value adjustment range undelayed short-circuit release	A	0
Type of electric connection		Flat plug-in connection
Number of contacts as normally open contact		0
Number of contacts as normally closed contact		0
Number of contacts as change-over contact		0
Suitable for power circuit breaker		Yes
Suitable for off-load switch		Yes
Suitable for motor safety switch		Yes
Suitable for overload relay		No