DATASHEET - IZMX-AS22-16-1



Signalling switch ON-OFF, 2W

Powering Business Worldwide*

Part no. IZMX-AS22-16-1 Catalog No. 184172 Alternate Catalog 67C2823G91

No.

EL-Nummer 4398515

(Norway)

Delivery program

zomony program	
Product range	Accessories
Accessories	Auxiliary contact
Accessories	Standard auxiliary switch for On-Off signaling
	The basic device already contains two changeover contacts. Mounting kit with 2 additional changeover contacts with cable lengths for IZMX16.
For use with	IZMX16 INX16
Instructions	Retrofit kit for IZMX16 circuit-breakers The retrofit kit includes the required SEC control cable terminals.
	2 changeover contacts

Technical data

Rated breaking capacity

Inductive load			
250 V AC	,	A	10
125 V DC	,	A	0.5
250 V DC	,	A	0.25

Design verification as per IEC/EN 61439

Technical data for design verification		
Operating ambient temperature min.	°C	-25
Operating ambient temperature max.	°C	70

Technical data ETIM 7.0

Technical uata ETIW 7.0						
Low-voltage industrial components (EG000017) / Auxiliary contact block (EC000041)						
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Auxiliary switch block (ecl@ss10.0.1-27-37-13-02 [AKN342013])						
Number of contacts as change-over contact			2			
Number of contacts as normally open contact			0			
Number of contacts as normally closed contact			0			
Number of fault-signal switches						
Rated operation current le at AC-15, 230 V		Α	10			
Type of electric connection			Flat plug-in connection			
Model			Integrable			
Mounting method			Other			
Lamp holder						