DATASHEET - IZMX-MIL3133C-F16-1



Mechanical interlock, TYPE 2, 31, 33, bowden cables, F



Part no. IZMX-MIL3133C-F16-1

Catalog No. 184207 Alternate Catalog 65A2840G34

No.

EL-Nummer 4398550

(Norway)

Delivery program

- control / programm	
Product range	Accessories
Accessories	Interlocks
Accessories	Mechanical interlock, fixed mounting
	Туре 33
	For 3 circuit-breakers with the same or different frame size: interlock: A, C against B. When B is off, A and C can be switched on. B can be switched on only when A and C are OFF. In addition, two IZMX-MIL-CAB cable kits with the desired length are required. Select the appropriate part no. for each circuit-breaker.
For use with	IZMX16 INX16
Installation type	Fixed

Design verification as per IEC/EN 61439

Technical data for design verification		
Operating ambient temperature min.	°C	-25
Operating ambient temperature max.	°C	70

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Mechanic interlock for switch (EC001044)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Mechanic interlock for switch (ecl@ss10.0.1-27-37-13-03 [AKN341013])			
Auxiliary contacts, extendable	No		
Number of contacts as normally closed contact	0		
Number of contacts as normally open contact	0		

Dimensions

