



Interlock, mechanical, type 32, Bowden cable, fixed

**Part no.** IZMX-MIL32C-F40-1  
**Catalog No.** 184211  
**Alternate Catalog No.** 65A2840G45  
**No.**  
**EL-Nummer (Norway)** 4398554

**Delivery program**

Product range		Accessories
Accessories		Interlocks
Accessories		Mechanical interlock, fixed mounting
		Type 32
		For 3 circuit-breakers with the same or different frame size: interlock: 2 against 1 / max. 2 ON. Any one or two circuit-breakers can be closed at the same time. In addition, three IZMX-MIL-CAB... cable kits are required. Select the appropriate part no. for each circuit-breaker.
For use with		IZMX40... INX40...
Installation type		Fixed

**Design verification as per IEC/EN 61439**

Technical data for design verification		
Operating ambient temperature min.	°C	-25
Operating ambient temperature max.	°C	70

**Technical data ETIM 7.0**

Low-voltage industrial components (EG000017) / Mechanic interlock for switch (EC001044)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Mechanic interlock for switch (ec1@ss10.0.1-27-37-13-03 [AKN341013])

Auxiliary contacts, extendable		No
Number of contacts as normally closed contact		0
Number of contacts as normally open contact		0

**Dimensions**



