DATASHEET - IZMX-MIL2C-W40-1

Part no. Catalog No.

EL-Nummer

(Norway)

No.



Mechanical interlock, TYPE 2, bowden cables, W

0004398558

IZMX-MIL2C-W40-1 184215 65A2840G40 Alternate Catalog



Delivery program

| Product range | Accessories |
|-------------------|---|
| Accessories | Withdrawable units |
| Accessories | Mechanical interlock |
| | Type 2 |
| | for 2 circuit-breakers: A normal power supply (A) and an emergency network supply (B). 1 set of cables also required in addition. |
| For use with | IZMX40W INX40W |
| Installation type | Withdrawable |

Design verification as per IEC/EN 61439

| Technical data for design verification | | |
|--|----|-----|
| Operating ambient temperature min. | °C | -25 |
| Operating ambient temperature max. | °C | 70 |

Technical data ETIM 7.0

| Low-voltage industrial components (EG000017) / Mechanic interlock for switch (EC001044) | | | |
|---|----|--|--|
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Mechanic interlock for switch (ecl@ss10.0.1-27-37-13-03 [AKN341013]) | | | |
| Auxiliary contacts, extendable | No | | |
| Number of contacts as normally closed contact | 0 | | |
| Number of contacts as normally open contact | 0 | | |

Dimensions

