



Door interlock in ON, IZMX40, cassette

Part no. **IZMX-DI400N-LW-1**
 Catalog No. **185711**

Delivery program

Product range			Accessories
Accessories			Interlocks
Accessories			door interlock
			<p>Door interlock mounting kit</p> <p>The door interlock is mounted on the cassette</p> <p>If the circuit-breaker is switched off and the control panel door is opened, the circuit-breaker will be locked in the OFF position.</p> <p>If the circuit-breaker is switched on while the door is closed, the control panel door will be locked.</p> <p>In case of emergency, the interlock can be released with a screwdriver. The interlock is located on the left side from the operator's viewpoint.</p>
For use with			IZMX40...W INX40...W
Installation type			Withdrawable

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Accessories for low-voltage switch technology (EC002498)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Component for low-voltage switch technology (accessories) (ecl@ss10.0.1-27-37-13-92 [AKN570013])			
Type of accessory			Mechanical locking