



**Main switch, 240 V, 40A, 4HP**

**Part no.** IS-40/4  
**Catalog No.** 276273  
**Alternate Catalog No.** IS-40/4  
**EL-Nummer (Norway)** 0001460825

Similar to illustration

### Delivery program

Basic function			Main load disconnecter switch
Number of poles			4 pole
Application			Switchgear for industrial and advanced commercial applications
Rated current	$I_n$	A	40
Product range			IS
Contact sequence			

### Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	$I_n$	A	40
Heat dissipation per pole, current-dependent	$P_{vid}$	W	1.9
Equipment heat dissipation, current-dependent	$P_{vid}$	W	2.8
Static heat dissipation, non-current-dependent	$P_{vs}$	W	0
Heat dissipation capacity	$P_{diss}$	W	0
Operating ambient temperature min.		°C	-5
Operating ambient temperature max.		°C	40

### Technical data ETIM 7.0

Devices for distribution board-/surface mounting (EG000062) / Main switch for distribution board (EC001545)			
Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Main switch for distribution board (ecl@ss10.0.1-27-14-23-01 [AFZ813014])			
Switching function			Other
Number of contacts as normally open contact			4
Number of contacts as normally closed contact			4
Number of contacts as change-over contact			0
Number of poles			4
Rated current		A	40
Rated voltage		V	240
Min. rated voltage		V	240
Rated switching capacity		kA	12.5
Short-circuit breaking capacity (Icw)		kA	2
Voltage type			AC
Forced segregation (according to DIN VDE 0113)			No
With signal lamp			No
Colour calotte			
Lamp type			
Lamp socket			
Max. lamp power		W	0
Width in number of modular spacings			4

Built-in depth	mm	69.5
Degree of protection (IP)		IP40

## Dimensions

