



Main switch, 240 V, 125A, 2HP

Part no. IS-125/2  
 Catalog No. 276287  
 Alternate Catalog No. IS-125/2  
 EL-Nummer (Norway) 0001460859

### Delivery program

Basic function			Main load disconnecter switch
Number of poles			2 pole
Application			Switchgear for industrial and advanced commercial applications
Rated current	$I_n$	A	125
Product range			IS
Contact sequence			

### Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	$I_n$	A	125
Heat dissipation per pole, current-dependent	$P_{vid}$	W	6.2
Equipment heat dissipation, current-dependent	$P_{vid}$	W	11
Static heat dissipation, non-current-dependent	$P_{vs}$	W	0
Heat dissipation capacity	$P_{diss}$	W	0
Operating ambient temperature min.		°C	-5
Operating ambient temperature max.		°C	40

### Technical data ETIM 7.0

Devices for distribution board-/surface mounting (EG000062) / Main switch for distribution board (EC001545)			
Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Main switch for distribution board (ecl@ss10.0.1-27-14-23-01 [AFZ813014])			
Switching function			Other
Number of contacts as normally open contact			2
Number of contacts as normally closed contact			2
Number of contacts as change-over contact			0
Number of poles			2
Rated current		A	125
Rated voltage		V	240
Min. rated voltage		V	240
Rated switching capacity		kA	10
Short-circuit breaking capacity ( $I_{cw}$ )		kA	2
Voltage type			AC
Forced segregation (according to DIN VDE 0113)			No
With signal lamp			No

Colour calotte			
Lamp type			
Lamp socket			
Max. lamp power		W	0
Width in number of modular spacings			2
Built-in depth		mm	69.5
Degree of protection (IP)			IP40

## Dimensions

