

Flange, closed, HxWxD=116x329x23mm



Part no. FL4-X
024355
EL Number 4132328
(Norway)

| General specifications | | |
|--|--|---|
| Product name | | Eaton xEnergy Safety Ci flange plate |
| Part no. | | FL4-X |
| EAN | | 4015080243557 |
| Product Length/Depth | | 23 millimetre |
| Product height | | 116 millimetre |
| Product width | | 329 millimetre |
| Product weight | | 0.284 kilogram |
| Compliances | | RoHS conform |
| Product Tradename | | xEnergy Safety Ci |
| Product Type | | Accessories |
| Product Sub Type | | Flange plate |
| Delivery program | | |
| Type | | Accessory for basic enclosures Basic enclosure xEnergy Safety Ci |
| Model | | Blind |
| Accessory/spare part type | | Flanges |
| Technical Data - Mechanical | | |
| Shape | | Straight |
| Unit type | | Modular system |
| Surface protection | | Untreated |
| Material | | Plastic |
| Degree of protection | | Other |
| Number of connector holes | | 0 |
| Cable entry type | | Drill as required |
| Thread type | | None |
| Suitable for nominal thread (PG) - min | | 16 |
| Suitable for nominal thread (PG) - max | | 50 |
| Additional information | | |
| Special features | | Sponge-rubber, captive gasket Quick mounting using wedge-lock fasteners (included as standard) |
| Used with | | 375 mm (enclosure dimensions) Basic enclosure Accessory for basic enclosures xEnergy Safety Ci |

Technical data ETIM 8.0

| Distribution boards (EG000023) / Gland plate for enclosure/cabinet (EC000211) | | |
|--|----|-----------|
| Electric engineering, automation, process control engineering / Electrical installation, device / Electrical distribution system (incl. small distribution board) / Gland plate for small distribution boards/switchgear cabinets (ecl@ss10.0.1-27-14-24-21 [ADI315007]) | | |
| Model | | Blind |
| Type | | Straight |
| Width | mm | 329 |
| Height | mm | 116 |
| Depth | mm | 23 |
| Material | | Plastic |
| Surface protection | | Untreated |
| Degree of protection (NEMA) | | Other |
| Pre-stamping | | No |
| Number of connector holes | | 0 |

| | | |
|---------------------------------------|--|---------|
| Thread type | | None |
| Suitable for nominal thread metric/PG | | 16 - 50 |