



**Grommets for conduits, degree of protection IP 65**

|   |  |   |
|---|--|---|
|  | <p><b>EDR 32</b></p> <ul style="list-style-type: none"> <li>Grommets for conduits</li> <li>for knockouts M 32</li> </ul> |  |
|---|--|---|

- conduit connection M 32
- bore-hole: Ø 32.5 mm
- wall thickness 1.5-3.2 mm
- for indoor - normal environment and (or) protected outdoor installation
- ambient temperature - 25 °C to + 35 °C
- glow wire test IEC 60695-2-11: 750 °C
- colour: grey, RAL 7035
- degree of protection: IP 65

|                |                      |
|----------------|----------------------|
| material       | TPE (-25° to +80°C)  |
| weight         | 0,008 kg             |
| glow wire test | IEC 60695-2-11 750°C |

**Drawings**

Dimension drawing



**Operating and ambient conditions**

|   |  |
|---|--|
| Application area                                | Suitable for indoor installation and outdoor installation, protected against weather influences  |
| Ambient temperature                             | Average value over 24 hours + 35 °C<br>Maximum value + 40 °C<br>Minimum value - 25 °C  |
| Fire protection in the event of internal faults | Demands placed on electrical devices from standards and laws<br>Minimum requirements<br>- Glow wire test in accordance with IEC 60695-2-11:<br>- 650° C for boxes and cable glands |
| Burning behaviour                               | Glow wire test IEC 60695-2-11: 750 °C<br>UL Subject 94: -<br>flame-retardant<br>self-extinguishing   |
| Toxic behaviour                                 | halogen-free<br>silicone-free<br>"halogen-free" in accordance with the examination of the cables and insulated wires - corrosiveness of fumes - as per IEC 60754-2                 |

Note: For material properties see technical data.