



Anybus Wireless Bolt product.

Anybus Wireless Bolt - Ethernet RJ45 PoE

Anybus Wireless Bolt enables you to connect industrial machines and devices to a wireless network. It is attached onto a cabinet or a machine to enable wireless access over Bluetooth®, Bluetooth Low Energy® or Wireless LAN (WiFi).



On the wired side, the Anybus Wireless Bolt communicates over Industrial Ethernet, supporting protocols such as BACnet/IP, PROFINET, EtherNet/IP, Modbus TCP as well as all TCP and UDP based protocols.

CONFIGURE MACHINES WIRELESSLY

Anybus Wireless Bolt gives you direct access to configure or troubleshoot your machinery. With a range of 100 meters you can access the internal web pages via a laptop, tablet or smartphone. BYOD (Bring Your Own Device) means that you no longer need an expensive HMI. A machine operator or technician does not need to be physically located at the machine to gain access.

AN ALL-IN-ONE SOLUTION

With Anybus Wireless Bolt you get an All-in-one package featuring, connector, communication processor and integrated antenna in the same unit, with an exterior IP67 protection class.

FEATURES AND BENEFITS

- Configure or troubleshoot industrial machinery over a wireless network
- Increase flexibility and mobility. Eliminate expensive fixed HMI's by using a laptop, tablet or smartphone
- Connect to moving field equipment such as AGV's (Automated Guided Vehicles)
- Fast Roaming (IEEE 802.11r), High link speed (IEEE 802.11n)
- Full compatibility with Anybus Wireless Bridge — a wireless product for cable replacement
- Connect to a Cloud Service of your choice or get live data and integrate it into a SCADA system
- Supports Ethernet and protocols such as: BACnet/IP, EtherNet/IP, Modbus-TCP, PROFINET, TCP/UDP
- Simultaneous operation of Bluetooth and Wireless LAN allowing for bridging between the two networks
- Security features for a secure industrial operation
- Dual power supply, PoE (Power over Ethernet) and/or 3-pole 19-36VDC connector
- Available with white top Sunbolt enabling 30% higher surrounding temperature compared to black in direct sunlight.
- Operation with Wireless LAN, Bluetooth classic and Bluetooth Low Energy.
- CLI (Command Line Interface) for configuration and diagnostics

WIRELESS LAN INTERFACE

- Wireless standards: WLAN 802.11 a, b, g, n, d.
- Operation modes: Access point or Client
- Wireless LAN bands: 2.4GHz and 5GHz

- RF output power: 18 dBm EIRP (including antenna gain 3dBi)
- Max number of slaves for access point: 7
- Power consumption: 54mA@24VDC
- Net data throughput: 20 Mbps. Link speed: max 65 Mbps (802.11n SISO)
- Security: WEP 64/128, WPA, WPA-PSK and WPA2, TKIP and AES/CCMP, LEAP, PEAP including MS-CHAP.

BLUETOOTH INTERFACE

- Wireless standards (profiles): PANU & NAP
- Operation modes: Access point or Client
- RF output power: 14 dBm EIRP (including antenna gain 3dBi)
- Bluetooth conducted sensitivity: -90 dBm
- Max number of slaves for access point: 7
- Power consumption: 36 mA@24VDC
- Net data throughput: ~1 Mbps
- Bluetooth version support: Classic Bluetooth v2.1
- Security: Authentication & Authorization, Encryption & Data Protection,
- Privacy & Confidentiality, NIST Compliant, FIPS Approved

BLUETOOTH LOW ENERGY INTERFACE

- Wireless standards (profiles): GATT
- Operation modes: Central or Peripheral (pending)
- RF output power: 10 dBm EIRP (including antenna gain 3dBi)
- Max number of simultaneous connections for Central:7
- Power consumption: 36 mA@24VDC
- Net data throughput: ~200 kbps
- Bluetooth Low Energy version: 4.0 dual-mode
- Security: AES-CCM cryptography

ETHERNET INTERFACE

- Supports Ethernet protocols: IP, TCP, UDP, HTTP, LLDP, ARP, DHCP Client/Server
- Supports wireless bridging of Industrial Ethernet protocols: BACnet/IP, EtherNet/IP, Modbus-TCP, PROFINET
- Ethernet interface: 10/100BASE-T with automatic MDI/MDIX cross-over
- Layer 2 bridging mode between Anybus Wireless Bolts or Bridges, Otherwise Layer 3 TCP/UDP bridging

Technical specifications

Dimensions	Diameter: 68 mm. Height: 75 mm without PS-connector, 84 mm incl. PS-connector. Outside height: 41 mm.
Weight	84g
Temperature Bolt (black)	Shadow: -40 to +65 °C Direct sunlight: -40 to +45 °C Storage temperature: -40 to +85 °C
Temperature Sunbolt (white)	Shadow and direct sunlight: -40 to +65 °C Storage temperature: -40 to +85 °C
Output Power	Wireless LAN 18 dBm EIRP - Bluetooth 14 dBm EIRP - Bluetooth Low Energy 10 dBm EIRP All including antenna gain 3dBi
Power supply	19-36 VDC and/or PoE DTE Type1 according to IEEE 802.3af

Power consumption	0.7W idle, 1.7W max (54mA@24VDC with Wireless LAN and 36mA@24VDC with Bluetooth)
Enclosure material	Top: Valox 357X(f1) PBT/PC. Suitable for outdoor use with respect to exposure to ultraviolet light, water exposure and immersion in accordance with UL 476C. Bottom: Celanex: XFR 6840 GF15. PBT glass reinforced plastic
Mechanical rating	IP66 and IP67 for top (outside the host), IP21 for bottom (inside the host)
Mounting	M50 screw and nut (50.5 mm hole needed)
Antenna	One internal antenna. Dual-band 2,4GHz and 5GHz.
Connector	RJ45 Ethernet/PoE and 3 pole screw connector for power
Vibration compatibility	Sinosoidal vibration test according to IEC 60068-2-6:2007 and with extra severities; Number of axes: 3 mutually perpendicular (X:Y:Z), Duration: 10 sweep cycles in each axes, Velocity: 1 oct/min, Mode: in operation, Frequency: 5-500 Hz, Displacement ± 3.5 mm, Acceleration: 2g. Shock test according to IEC 60068-2-27:2008 and with extra severities; Wave shape: half sine, Number of shocks: ± 3 in each axes, Mode: In operation, Axes $\pm X,Y,Z$, Acceleration: 30 m/s ² , Duration: 11 ms.
CERTIFICATIONS	
Europe	ATEX Category 3, zone 2 according to EN60079-15, product marking: EX II 3 G nA IIC T4 Gc. CE, 2014/53/EU Radio Equipment Directive (RED)
USA	FCC 47 CFR part 15, subpart B. UL: Ind. Cont. Eq. also Listed Ind. Cont. Eq. for Haz. Loc. CL1, DIV 2, GP A,B,C,D, T4. UL file: E203225
Canada	ICES-003
Japan	MIC
Other countries	Brazil, Australia, Colombia, Turkey, Malaysia, Argentina, India, China, Korea, United Kingdom, Russia

File	Version	Size	Read online
------	---------	------	-------------

Content of delivery

AWB2030 Bolt RJ45 PoE (black top) / AWB 2031 Sunbolt RJ45 PoE (white top)
Quick start documentation

Optional Accessories

AWB4005: PoE Injector 100-240 VAC

AWB4006: PoE Injector 12-57 VDC

AWB4707: Power Supply 90-264 VAC to 24VDC 19W world socket kit, 1,4 meter cable and 3-pole Bolt power connector (**Only** for Bolt RJ45 PoE)

AWB4708 - Bolt base Protector; Read more about the base protector [here](#).

AWB4709 - Bolt base Protector and Mounting Bracket kit; Read more about the base protector [here](#).

024715 - Replacement Power plugs for Anybus Wireless Bolt, bag with 5pcs, 3-pin with screw terminals and screw fastening, symbols +-PE

AWB2330 (BOLT RJ45 STARTERKIT)

2 x Wireless Bolts RJ45 (AWB2030), 2 x Power Supply (world), power cables, Quick Start Guide.

3 year guarantee.

(Limitation: Max one Starterkit per customer)

Ordering Information

Order code	
	AWB2030 (Bolt RJ45 PoE)
	AWB2031 (Sunbolt RJ45 PoE)

3 year guarantee. For purchasing instructions and terms and conditions, see: → [How to buy](#)

Copyright © 2020 HMS Industrial Networks - All rights reserved.